



DESCRIPTION OF STANDARD UNIT:

- Construction of powder-coated steel
- MDF front panel and sides
- Front and side glasses with heaters
- Side and front glasses with silver serigraphy
- Silver finishes
- Stainless steel worktop
- Night blind
- White lighting
- Wheels
- Forced cooling
- Temp. range*: $-12 \div -22^{\circ}\text{C}$
- Automatic defrosting
- Automatic water evaporation

OPTIONS:

- LED lighting
- Ice-cream containers
- Spoon washer
- For individual decoration (DZ)
- Wooden casing (OD)
- SIBU front panel
- Highlighted Plexiglas front
- Water cooled condenser (SW)
- Lift up system of front glass (TL)

* Temperature range given for maximum ambient temperature of $+30/+32^{\circ}\text{C}$ and relative humidity 50/55%, except **BT 24** - temp. range given for max ambient temp. of $+25^{\circ}\text{C}$ and relative humidity 60%.

TECHNICAL DETAILS:

Type: K-1 BT	Length [mm]	Depth [mm]	Height [mm]	Containers quantity* [pcs.]	Weight [kg]	Daily consumption [kWh/24h]	Electrical input power: working cycle** /defrosting cycle*** [W]
12	1160	1150	1300	2x6	200	26,0	1500/2600
18	1660			2x9	280	29,0	1800/3300
24	2160			2x12	330	39,0	1900/3500

* For containers 165x360x150(h) mm – 5,0 l

** Values are provided for an evaporation temp. of -35°C , condensation temp. of $+45^{\circ}\text{C}$, ambient temp of $+30^{\circ}\text{C}$ and relative humidity of 55%.

*** Values are provided for an evaporation temp. of -25°C , condensation temp. of $+45^{\circ}\text{C}$, ambient temp of $+30^{\circ}\text{C}$ and relative humidity of 55%.