

J 7 EXTRA R507 (COD. 0000016070300)



Negative - static scooping display cabinet

Technical data

| | |
|---|--|
| Temperature | -15°C -20°C |
| Voltage and Frequency | 230 Volt 50 Hz |
| Gas | R404A |
| Net dimension | 1341 x 723 x 1224 mm (w x d x h) |
| Packed dimension | 1460 x 780 x 1325 mm (w x d x h) |
| Packed dimension (disassembled glass canopy) | 1460 x 780 x 1030 mm (w x d x h) |
| Gross capacity | 317 dm ³ |
| Net capacity | 131 for displaying ice cream and 133 in the reserve |
| Gross weight | 162 Kg |
| Net weight | 117 Kg |
| Heat insulation | In polyurethane injected "HCFC/CFC" free |
| External cabinet | Plasticised steel sheet |
| Inner tank | White prepainted non-toxic steel sheet |
| Frame | In plastica stampata riscaldada |
| Glass | Insulating Upper curved glazed cabinet |
| Side grid - colour | Plastica stampata |
| Back grid - colour | plasticised steel rod |
| Compressor | 647 Frig/h T.E. -23,3°C |
| Consumo a regime | 470 Watt |
| Defrosting power consumption | 570 Watt |
| Condensator | Packed system (finned) with powered fan |
| Evaporator | Static packed evaporation system (and defrosting resistance) + evaporator coil foamed on the walls |
| Climatic class - EN 441 | 4 (30°C 55% R.H.) |
| Plug | European - Angular Plug |
| Thermometer | Mechanic |
| Thermostat | Mechanic |
| Standard equipment | Separate reserve accessible via a door - 4 wheels - light with switch |
| Optional | Stainless steel containers - Portions-washing - basket - electronic control |
| Brand | FRAMEC |
| Producer brand | MONDIAL GROUP |

The manufacturer will reserve the right to make any modification without prior notice.

| | | | |
|---------|------------|------------|-------------|
| Version | Updated on | Written by | Approved by |
| 1 | 09/10/2007 | D. Capuano | R. Bovo |